



W-Band Power Amplifier, 90 to 100 GHz, 30 dB Gain, 15 dBm P_{1dB}

Description:

Model SBP-9031043015-1010-E1 is a power amplifier with a typical small signal gain of 30 dB and a nominal output power of +15 dBm across the frequency range of 90 to 100 GHz. The DC power requirement for the amplifier is +15 V_{DC}/190 mA. The mechanical configuration offers an in line structure with WR-10 waveguides and UG-387/U-M anti-cocking flanges. Other port configurations, such as with 1 mm connectors or a right angle structure with WR-10 waveguides, are also available under different model numbers.



Features:

- High Gain
- High Output Power

Applications:

- Radar Systems
- Communication Systems
- Test Equipment

Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Frequency	90 GHz		100 GHz
Gain		30 dB	
P _{1dB}		+15 dBm	
P _{sat}		+20 dBm	
P _{in}			-5 dBm
Input Return Loss		10 dB	
Output Return Loss		10 dB	
DC Voltage	+13 V _{DC}	+15 V _{DC}	+16 V _{DC}
DC Supply Current		190 mA	
Specification Temperature		+25 °C	
Case Temperature	0 °C		+50 °C

Mechanical Specifications:

Item	Specification
Input Port	WR-10 Waveguide with UG-387/U-M Anti-Cocking Flange
Output Port	WR-10 Waveguide with UG-387/U-M Anti-Cocking Flange
Bias	Solder Pin
Case Material	Aluminum
Finish	Gold Plated
Weight	1.6 Oz
Size	1.10" (W) X 1.50" (L) X 0.75" (H)
Outline	BG-SW-2-A






W-Band Power Amplifier, 90 to 100 GHz, 30 dB Gain, 15 dBm P_{1dB}

Typical Gain and Return Loss vs. Frequency

Bias: +15 V_{DC}/190 mA



Typical Output Power vs. Frequency

Bias: +15 V_{DC}/190 mA

