



24.125 GHz Doppler Sensor Head, Single Channel, Long Range

Description:

Model SSS-24310-22L-S1 is K Band, lens antenna-based Doppler sensor head that is designed and manufactured for **long range** measurements of a moving target's speed. The sensor head has a center frequency of 24.125 GHz and takes a nominal bias of +5.0 VDC/250 mA. The sensor heads are configured with a lens corrected antenna, T/R diplexer, a single channel receiver and a transmitter/receiver oscillator in an integrated package. Sensor heads with a dual receiver are offered under model number **SSS-24310-22L-D1** and can detect both the speed and direction of a moving target.



Features:

- 24.125 GHz Operation
- Low Flicker Noise and High Sensitivity
- Low Harmonic Emission

Applications:

- Traffic Management Systems
- Microwave Fence
- Military Surveillance Systems

Electrical Specifications:

Parameter	Minimum	Typical	Maximum
Antenna 3 dB Beamwidth		12°	
Antenna Side Lobes		-20 dB	
Antenna Gain		22 dBi	
Antenna Polarization	Right-Handed Circular		
RF Frequency Range	24.000 GHz	24.125 GHz	24.250 GHz
Transmitting Power		+10 dBm	
IF Frequency Range	DC		100 MHz
IF Offset Voltage		$\pm 0.25 V_{DC}$	
Frequency Stability		-0.8 MHz/°C	
Power Stability		-0.03 dB/°C	
DC Supply Voltage		+5 V _{DC} /250 mA	
Specification Temperature		+25°C	
Case Temperature	-40°C		+85°C



24.125 GHz Doppler Sensor Head, Single Channel, Long Range

Note:

- SAGE Millimeter, Inc. reserves the right to change the information presented without notice.

Caution:

- The device is static sensitive. Always follow ESD rules when working with the device.
- Wrong bias or reverse bias on the sensor will damage the device.
- Exceeding absolute maximum ratings shown will damage the device. Use additional heatsink or fan if necessary.

